



PercoTop®

CS440 Silicone Remover / CS400 Multicleaner

Description

- PercoTop® CS440 Silicone Remover is a slowly evaporating organic solvent mixture, and PercoTop® CS400 Multicleaner a fast evaporating mixture.
- Both products are used primarily to remove oil and grease residue.

Products

CS440	PercoTop® CS440 Silicone Remover
CS400	PercoTop® CS400 Multicleaner

Surface preparation

- Apply PercoTop® CS440 Silicone Remover or PercoTop® CS400 Multicleaner with a spray bottle or clean cloth.
- Wipe dry with a clean cloth before the silicone remover/multicleaner evaporates.

Remarks


Special remarks

- Allow cleaned surface to dry completely before further treatment.
- Do not allow the silicone remover/multicleaner to dry on the surface (wipe on and directly wipe off).
- Both products are not suitable for cleaning spray guns or tools.
- Always use a clean cloth.
- Heavily soiled parts must be cleaned twice.

For professional use only!

PercoTop®

CS440 Silicone Remover / CS400 Multicleaner

Note on safety:	
	This product is classified according to regulation (EC) 1272/2008 (CLP). Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protection equipment during application.
Observe the precautionary notices displayed on the container.	

Product data

	PercoTop® CS440 Silicone Remover	PercoTop® CS400 Multicleaner
Flash point	+ 26°C	+ 4°C
VOC content 2004/42/IIIB(a)(850)770	The EU limit value for this product (product category IIB.a) in ready for use form is max. 850 g/l of VOC.	
	The VOC content of this product in ready for use form is max. 770 g/l.	The VOC content of this product in ready for use form is max. 750 g/l.

<p>Information</p> <p>The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Axalta cannot anticipate all variations in actual end-use conditions Axalta makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights.</p> <p>This Technical Data Sheet supersedes all previous issues.</p>

<p>Copyright © 2018, Axalta Coating Systems, LLC and all affiliates. All rights reserved. The Axalta logo, Axalta™, Axalta Coating Systems™ and all products denoted with ™ or ® are trademarks or registered trademarks of Axalta Coating Systems, LLC and its affiliates. Axalta trademarks may not be used in connection with any product or service that is not an Axalta product or service.</p>
